One Way Vision Eco UV

One way vision eco uv

- UV printable
- Indoor & outdoor window ads.
- Removable glue
- LaminatedOPPfilm(Additional Liner)

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
PVC		
Type	/	Calendered monomeric soft PVC film
Thickness	/	180±10um/7mil
Color	/	Ceramic Clear
Back	/	Black
Shrinkage	/	≤0.6%
Surface Tension	/	≥30dn/cm
Opacity	/	>99%
Holes No.	/	Average 130/sq in
Hole Diameter	/	1.6mm
Distance Between Holes	/	2.4mm
Hole Space	/	41%
Adhisive		
Type	/	Clear solvent based removable pressure sensitive glue
Weight(g/㎡)	/	30±2
Adhesion Temperature	/	15℃~40℃
Peeling Force	GB2792-81 China National Standard	≥4.5N/25mm 20min
Initial Adhesion- Ball Tack	GB4852-84	≥5# Steel Ball
Holding Power	GB4854-84	≥800min
Removable Durability	/	One year cleanly removable glue on clean glass surface at temperature of 23~25℃ and RH of 50~60%
Liner		
Type	/	Laminated OPP film(Additional Liner)
Color	/	White
Weight	/	90g±5g/㎡ 2.6oz/sq.yd
Release Force	/	0.2±0.1N/25mm
Available Size	/	36"/42"/50"/54"/60" 50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
□	□	□	□
Screen Printing	**Dye Sublimation Transfer**	**Dye Sublimation Direct**	**Water based**

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability.
The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

MAEGIS B.V. · Midzomerweg 51 · 7532 SW Enschede · Nederland
Tel 0031 (0) 53 460 90 50 · Fax 0031 (0) 53 460 90 51 · info@maegis.nl · www.maegis.nl