

Texprint Wallcover Greyback



Product: ST-221U

Features:

- New developed fabric with woven textured white surface and rough grey back, both sides with PA coating
- Application as wall covering with glue on both rough and smooth wall, very easy to operate
- Good flatness and perfect opacity, makes it also ideal choice for Roll up, frame, etc
- Can be printed by UV, solvent, eco-solvent and Latex inks

Applications:

Wall covering

Roll Up Display

Frame

Art Decoration

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	330 g/sq.m	9.7 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A		Woven
Shielding Rate	ANSI PH2.19, ISO 5/2		99%
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1		DIN 4102-1-B1, NFPA 701 Test1
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
		<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.