



APPLICATION TABLE

FOR GLAZING EXPOSED TO THE SUN
SOLAR PROTECTION AND MIRROR FILM



● SINGLE GLAZING

●● DOUBLE GLAZING



		CLEAR GLAZING FROM 4 TO 10 MM	TINTED
		TEMPERED	LAMINATED
			ARMORED
			DOUBLE GLAZING OVER 1,20 SQM
			DOUBLE GLAZING CLEAR UNDER 1,20 SQM
			DOUBLE GLAZING LAMINATED OR TINTED
Outside application	SOL 102 / SOL 108 / SOL 112 SOL 142 / SOL 152 / SOL 162 SOL 172 / EXT 600	✓	✓
Inside application	IR 50 / IR 80 / SOL 145 SOL 148 / EXT 600	✓	✓
Inside application	SOL 101 / SOL 111 / SOL 141 SOL 151 / SOL 161 / SOL 171 SOL 275 / STS 160	✓	✗
Inside application	MIR 500 / MIR 900 / MIR 600 / MIR 800 / MIR 501 / MIR 502 / MIR 502 / MIR 503 / MIR 504 / MIR 505 / MDN 500	✓	✗
Outside application	MIR 500X / MDN 500X	✓	✓

Outside application
Inside application
Inside application
Inside application
Outside application